

TECHNICAL DATA - FLATBED DIECUTTERS - **WW** TYPE:

PARAMETER:		WW/MW 777	WW/MW 1000	WW/MW 1250
TABLE WIDTH/LENGTH	mm	777/ 2x1250	1000/ 2x1500	1250/ 2x1600
FEED RATE	cm/s	61	61	56
MAXIMUM ROLL GAP	mm	170	170	140
PRACTICAL EFFICIENCY	sheets/hour	200-250/300-440	200-250/300-440	300-440
DIMENSIONS (LENGHTxWIDTHxHEIGHT)	mm	3000x1110x1250	3000x1470x1250	3500x1570x1250
WEIGHT	kg	430	490	560

TECHNICAL DATA - FLATBED DIECUTTERS - **MW** TYPE:

PARAMETER:		MW 1400	MW 1600	MW 1800	MW 2000	MW2400
TABLE WIDTH/LENGTH	mm	1390/ 2x1600	1590/ 2x1910	1790/ 2x1910	1990/ 2x2165	2390/ 2x2420
FEED RATE	cm/s	48	48	56	56	56
MAXIMUM ROLL GAP	mm	170	170	140	140	140
PRACTICAL EFFICIENCY	sheets/hour	300-440	300-440	300-440	300-440	300-440
DIMENSIONS (LENGHTxWIDTHxHEIGHT)	mm	3500x1720x1250	3920x1920x1250	3920x2120x1250	4430x2320x1250	4940x2720x1250
WEIGHT	kg	600	660	720	840	980